

## Filter-Cell - Art. No.:60 100

- » Compact
- » Plug and play installation



### Applications

- » Low to medium levels of smoke and dust
- » Occasional to frequent use
- » For exhaust hoods, extraction tables and robot cells

### Benefits

- » Space-saving due to compact design
- » Easy installation since unit is delivered ready to plug in ("plug and play")
- » Maintenance door allows easy filter change
- » Increased safety due to filter monitoring
- » Service life extension by selecting the optional bag filter

### Properties

- » Filter monitoring
- » 250 mm duct connector
- » Height-adjustable feet
- » Activated charcoal filter (optional)

### Variants

- » Other voltages

### Technical Data

<b>Art. No</b>	<b>60 100</b>
<b>Filter</b>	
Filter stages	2
Filter method	Disposable filter
Filter surface	ca. 15.8 m <sup>2</sup>
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filterclass	F9
Additional filters	Pre-filter (aluminum)
<b>Basic data</b>	
Extraction capacity	1,400 m <sup>3</sup> /h
Dimensions (w x d x h)	655 x 655 x 1,370 mm
Weight	150 kg
Motor power	1,5 kW
Power supply	3 x 400 V / 50 Hz
Rated current	3.2 A
Noise level	71 dB(A)
<b>Additional information</b>	
Fan type	Radial fan

